

CLAIMS:

1. An optical coherence tomography system comprising
 - an optical source to emit an optical beam
 - a sample space
 - a photodetector
 - 5 – an interferometer set-up including
 - a reference reflector and
 - a beam splitter-combination arrangement to
 - split the optical beam into a reference beam to the reference reflector and a sample beam to the sample space and to
 - 10 – combine a reflected beam from the reference reflector with a returning beam from the sample space on the photodetector, wherein
 - the optical source has an emission wavelength in the range of 1.6 μ m to 2.0 μ m, in particular having an infrared emission predominantly at a wavelength of 1.8 μ m associated with a transition between an upper energy level and a lower energy level
 - 15 and
 - the optical source comprises an excitation system which generates stimulated emission from a pump level to the upper energy level.
2. An optical coherence tomography system as claimed in Claim 1, wherein the optical source includes a Tm-doped fibre placed in an optical cavity of cavity reflectors facing one another.
- 20 3. An optical coherence tomography system as claimed in Claim 2, wherein the cavity reflectors are anti-reflex coated for a wavelength range of 760nm to 810nm.
- 25 4. An optical coherence tomography system as claimed in Claim 2 or 3, wherein the cavity reflectors have a high-reflectivity (coating) for the wavelength range 2.2 μ m to 2.4 μ m.

5. An optical coherence tomography system as claimed in Claim 2,3 or 4 wherein the cavity reflectors have a high-reflectivity (coating) for the wavelength range 2.2 μ m to 2.4 μ m and/or for the wavelength range 1.40 μ m to 1.5 μ m.
- 5 6. An optical coherence tomography system as claimed in Claim 2, wherein the optical cavity has reflectivities less than 0.04 for the wavelength range of 1.6-2.0 μ m.
7. An optical coherence tomography system as claimed in Claim 6, wherein
- 10 – an input cavity reflector has a high reflectivity (coating) for the wavelength range 1.6 μ m to 2.0 μ m and
- an output cavity reflector has a low-reflectivity (coating) for the wavelength range 1.6 μ m to 2.0 μ m.
8. An optical amplifier comprising
- 15 – a Tm-doped fibre in an optical cavity of cavity reflectors facing one another, wherein
- the cavity reflectors have an antireflex coating for the wavelength range of 1.6 μ m to 2.0 μ m, and in particular are anti-reflex coated for a wavelength of 1.8 μ m.
9. A Tm-doped fibre having a fibre core extending along a longitudinal axis of
- 20 the fibre and having a double cladding surrounding the fibre core.